

Service Bulletin

Date: February 2, 2026
Update Number: S2026-01
Subject: LiftMaster Security+ 3.0 HomeLink Update
Product Affected: HomeLink

Overview:

We have received numerous HomeLink related questions from the field and are documenting the pairing process for Security+ 3.0 to provide clear and consistent guidance.

Please note that Security+ 3.0 operators are compatible with HomeLink versions 4, 5, and 6, which generally apply to model year 2016 and newer vehicles; however, compatibility may vary by vehicle make and model.

The programming process may differ slightly from what you are accustomed to, as pairing is performed using the “EZ-Train” process outlined below. The most important distinction is becoming familiar with pairing HomeLink using the remote transmitter, rather than directly through the garage door opener (GDO) learn button

Important Requirements to Know Before Pairing with HomeLink®

- HomeLink® must be trained using the Security + 3.0 remote — **Do not use the garage door opener’s ‘Learn button.’**
- The remote must be paired with the operator before starting HomeLink® programming.
- Use the specific remote button already paired to the operator (Button 1, 2, or 3). This same button must be used when training HomeLink®

[Click here to view our LiftMaster HomeLink Video Tutorial](#), or read our step-by-step instructions below.

Programming Steps

1. Select the Button to Program

- a. Press and release the HomeLink® button you want to program. The LED should begin flashing slowly.
 - i. *Note: If you have the older HomeLink model (HL4) you must press and hold the HL button while adapting the HomeLink model.*
- b. If the LED rapidly flashes and then goes out (please note the following):
- c. This indicated the HomeLink button being programmed already has a learned remote signal. If this occurs, either:
 - i. Override the programmed button by pressing and holding that specific button until the HomeLink LED begins flashing slowly, then release. Or the following,
 - ii. Clear all HomeLink buttons.
 - iii. *Note: Steps 2 & 3 must be completed within 90 seconds of starting.*

2. Program the HomeLink® Button

- a. While the HomeLink® LED is flashing slowly
 - i. Hold your garage door remote close to the HomeLink® button.
 - ii. Press and hold the remote’s button until the HomeLink® LED changes from a slow blink to a rapid flash (the LED color will also change to green).
 - iii. Release all buttons once the LED flashes rapidly.

3. Complete and Test the Programming

- a. Press and hold the programmed HomeLink® button for 3-5 seconds.
- b. If the garage door begins to move on the 2nd button press, the programming was successful.

Service Bulletin

Important Compatibility Information

- Compatibility with Security + 3.0 Operators
 - This opener is compatible with HomeLink® versions 4, 5, and 6, generally found in 2016 and newer vehicles. Compatibility may vary by vehicle make and model.

Quick Tip: Identifying HomeLink® Version 4 and Above

- HomeLink® Version 4 and above can be identified in either of the following ways:
 - **Green Rapid Flash:** When successfully training to a remote signal, the HomeLink indicator changes to a green rapid flash.
 - **Simple Press & Release:** A quick press and release of an empty HomeLink button causes the system to enter slow blink training mode, which is characteristic of Version 4+ systems.

Resources and Support:

- LiftMaster HomeLink Video: [HomeLink to Sec+3.0](#)

Thank you for your continued support of LiftMaster. If you have any questions regarding the information above, please contact your LiftMaster Sales Representative.